
моtive





Vehicle Gateway

Motive's Vehicle Gateway uses built-in cellular connectivity to continuously sync driver and vehicle data with the Motive's Driver App and Fleet Dashboard. Other Vehicle Gateway capabilities include live GPS tracking, real-time maintenance monitoring, and up-to-date compliance records.

Key benefits

All-in-one

The Vehicle Gateway is one part of Motive's integrated solution to manage your vehicles, assets, drivers, and equipment.

Durable hardware


Built to perform even in harsh environments and remote working conditions. Backed by a 5-year warranty.

Accurate, reliable

Designed to power your central fleet management dashboard with accurate, live operational data from day one.

Live GPS tracking

With live updates as frequent as every two seconds, you can follow your crew as they move down the road.



AI Dashcam and Smart Dashcam integration

Use one tool to manage driver safety and compliance. Combining video and telematics data, you get a complete picture of what happened on the road.

🔓 LH120 Peterbilt

Location: Scenic Hwy N Snellville, GA In Motion for 1h 10m

Speed: 68 mph Fuel: 83% DEF: 60%


Dashcam




Telematics

Captures speed, fuel, fault codes, barometric pressure, battery voltage, coolant temp, engine intake temp, engine load, and more to the Motive platform

🗔 LH120 Freightliner





З


Motive

The device has been updated!

Updated few minutes ago

Asset Gateway pairing

Motive's Asset Gateways and Vehicle Gateways pair automatically so you can see which vehicle is hauling a particular asset in real-time.



Vehicle Gateway connectivity

Smartphone/tablet/ driver logbook app 5-year warranty

Cellular network AT&T 4G LTE with 3G fallback North America


GPS location services

GNSS location support with industry-leading location update frequency of 2 sec.


Supported AUX lines

2 Digital inputs

Vehicle diagnostic port




J1962 (OBD-II)




J1708 (6-pin)


J1939 (9-pin)


Supported vehicle-specific connections






TMC RP 1226








Proprietary Mack 2013-2018

Proprietary Volvo and Mack 2018+



Proprietary Freightliner (varies by model and year)

Environmental	Operating temperature -40°F–185°F (-40°C–85°C)	Automotive conditions SAE 1455
Software	 Features All log data transmitted via Bluetooth® or USB for compliance without cellular reception All traffic encrypted to the cloud Access to Motive cloud platform 	 All updates are pushed Over-The-Air seamlessly Support Android and iOS via mobile app SAE: J1708/J1587, J1939, J1962, J1979, J1850 (Autotap)
Hardware	 Unit lifetime 5-year warranty Memory Up to 4 Months of Log Data Storage temperature Internal Li-Ion for improved reliability when power is interrupted (LBB 3.55) Internal Li-Ion for improved reliability and real time disconnect alerts if gateway is unplugged or power is interrupted (LBB 3.6) 	GNSS Supports most systems including GPS and GLONASS Accessories • Motive Asset Gateway • Motive Asset Gateway • Motive Smart Dashcam • Motive Al Dashcam • Motive Cables • Motive Cables • Motive Autotap • SafetyDirect by Bendix CVS Cable • Motive AUX/PTO cable
Power	Voltage (power) 8V-32V Power consumption (vehicle on) 1.55W-5.5W	Sleep mode <30mA Voltage (AUX inputs) 2.2V-48V
@	<u>&</u>	
gomotive.com	855-434-3564	sales@gomotive.com